



Specifications and features

- ▶ Temperature range from approx. 5°C above ambient to boiling point, temperature regulation through tension thermostat. Heating element protected by over-temperature cut-out.
- ▶ 1023: bath, cover frame and perforated floor above the heating element are made of stainless steel.
- ▶ 1023: the adjustable water level regulator is situated at the back of the unit. It is part of the standard scope of supply, as well as the set of rings made of heat-resistant plastic material.
- ▶ 1023: outer housing made of electrolytically galvanised sheet steel, powder-coated.
- ▶ 1031/1032: bath, removable recessed lid with holes and perforated floor above the heating element are made of stainless steel.
- ▶ 1031/1032: the adjustable water level regulator at the right-hand side of the unit is part of the standard scope of supply.
- ▶ 1031/1032: the openings in the lid are covered by sets of rings made of heat-resistant plastic material.
- ▶ 1031/1032: four non-slip plastic feet ensure great stability.

Application

Water Baths for fume hoods 1031 / 1032 are special baths that are preferably used for protected applications in fume hoods (digestories).



1031 Water Bath for fume hoods

1032 Water Bath for fume hoods

Technical data

Model Order No.	Openings with sets of rings	Ø of the openings mm	Working height † mm	Exterior dimensions			Electrical connection*	Weight approx.		Packing volume approx. m ³
				Width mm	Depth mm	Height mm		net kg	gross kg	
1031	6	90	100	430	300	155	230 Volt / 50...60Hz / 1.5 kW	6.1	7.4	0.05
1032	8	110	100	670	300	155	230 Volt / 50...60Hz / 1.5 kW	8.2	10.2	0.24

† perforated floor to upper rim

* Special voltages available on request